

PHILIPS

Lighting



Xitanium LED downlight and spotlight drivers

Xitanium 36W/m 0.3-1.05A 52V 230V

Xitanium LED drivers are leading the way in terms of reliability

Product data

General Information	
Lighting Technology	LED
Operating and Electrical	
Output Current Ripple (Max)	4 %
Output Current (Max)	1050 mA
Open Circuit Voltage (DC) (Max)	60 V
Output Power (Max)	36 W
Output Power (Min)	11 W
Output Current (Min)	300 mA
Output Voltage (Max)	52 V
Output Voltage (Min)	24 V
Protection class IEC	Safety class I/II
System characteristics	
Central DC Operation	Yes
YellowDot ready	No
Temperature	
T-Case Lifetime (Max)	80 °C

T-Case Maximum (Max)	80 °C
Controls and Dimming	
Dimmable	No
Control Interface	Fixed
Mechanical and Housing	
Product Length	97 mm
Housing	Mini 97x43x30 4p2p
Overall length	97.2 mm
Overall width	43 mm
Overall height	30 mm
Dimensions (Height x Width x Depth)	30 x 43 x 97 mm
Ingress protection code	IP20 [Finger-protected]
Net Weight (Piece)	0.110 kg
Approval and Application	
Isolation Classification	Class I and Class II
Approval Marks	CE marking CB Certificate ENEC certificate CCC certificate RCM compliance

Xtanium LED downlight and spotlight drivers

Output Current Set Options	LEDSet
Product Data	
Order product name	Xtanium 36W/m 0.3-1.05A 52V 230V
Full product name	Xtanium 36W/m 0.3-1.05A 52V 230V
Full product code	871869682931800
Order code	929001436206

Material Nr. (12NC)	929001436206
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718696829318
Numerator - Packs per outer box	20
EAN/UPC - Case	8718696829325

