

PRODUCT DATASHEET

ORBIS SQUARE CLICK SENSOR 430 50W

ORBIS CLICK SENSOR | c



Areas of application

- Corridors, entrance areas

Product benefits

- Easy and quick installation

Product features

- Luminaires activated by sensor mode or conventional wall switch
- Operating mode easily changed by three clicks of wall switch
- Motion sensor (microwave technology) with adjustable detection parameters



TECHNICAL DATA

Electrical data


Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.70
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	3700 lm
Total luminous flux of contained light sources	6500 lm
Luminous efficacy	74 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcn
Beam angle	120 °

Dimensions & Weight

Length	430.00 mm
Width	430.00 mm
Height	80.00 mm
Product weight	1395.00 g



Materials & Colors

Product color	White
---------------	-------

Housing color	White
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...40 °C
Type of connection	Push button terminal, 2-pole
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

Sensor

Type of sensor	Light / Motion
Sensor technology	Microwave
Sensor controlled switching time	5 s...30 min
Detection range of motion sensor	2...6 m
Detection threshold of daylight sensor	2...50 lx

Certificates & Standards

Standards	CE / EAC / REACH / RoHS
-----------	-------------------------

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

DOWNLOAD DATA



User instruction

DOWNLOAD DATA



Tender documents



Declarations of conformity



Packaging insert

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075472822	Shipping box 5	737 mm x 557 mm x 570 mm	12126.00 g	233.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

