

Y-CONNECTOR SCREW | Branching for light management systems



Areas of application

- Suitable for all OSRAM components with modular 4p4c connector system

Product benefits

- For parallel connection of sensors to a MULTieco, MULTI 3, DALieco system
- Enables synchronization and connection of multiple EASY system components


Product features

- Passive distributor
- Connection via 2x four-pole screw terminal or modular 2 x 4p4c-connector
- Type of installation: Adhesive pad mounting on smooth surfaces

Product datasheet

Technical data

Dimensions & weight



Length	40.0 mm
Width	20.0 mm
Height	16.0 mm
Product weight	100.00 g





Certificates & standards

Type of protection	IP20
--------------------	------

Equipment / Accessories

– 2 connecting cables included, modular 4p4c connector on both ends, length 2.1 m

Download Data

File	
	Brochures Non-system-specific components brochure
	Brochures Application Guide EASY lighting control (GB)
	Declarations of conformity LMS MULTI3 SENSORS
	Installation/Operation notice Y-CONNECTOR SCREW branch element with screw clamps

Logistical Data

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321916686		Shipping carton box 25	224 mm x 190 mm x 220 mm	9.36 dm ³	2965.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.