

# PRODUCT DATASHEET SMART + WIFI PLANON 600X600

SMART+ Planon Frameless TW | Frameless panel luminaires with WiFi technology



#### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

#### **Product benefits**

- Easy and quick installation

## **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Dimmable
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Network protocol: WiFi



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	40.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	198.000 mA
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	II .
Operating mode	Mains voltage

# Photometrical data

Luminous flux	3400 lm
Total luminous flux of contained light sources	4250 lm
Luminous efficacy	85 lm/W
Color temperature	30006500 K
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Photobiological safety group acc. to EN62778	RGO
Photobiological safety group acc. to EN62471	RGO
Beam angle	110°

# **Dimensions & Weight**

	Length	600.00 mm
	Width	600.00 mm
Ī	Height	62.00 mm
	Product weight	4860.00 g

## Materials & Colors

Product color	White



Housing color	White
Body material	Aluminum
Cover material Polymethylmethacrylate (PMMA)	
Light emitting surface material	РММА
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

## **Application & Mounting**

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable
With light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	15000

## Certificates & Standards

Standards	CE / EAC / REACH / RoHS
Luminaire with limited surface temperature, "D sign"	No

# Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
----------------	--

# **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

# DOWNLOAD DATA



	DOWNLOAD DATA
PDF	User instruction
POF	Declarations of conformity

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075484443	Shipping box 3	682 mm x 308 mm x 690 mm	17618.00 g	144.94 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

